

TMF10L - TMF10K

Main Specifications

Mast

Mast type	CF100	
Total length mm	5 300	5 550
Feed motion length mm	3 730	
Feed shifting length mm	600 - 1 000	

Rollover

Rollover type	360 °	
Tip cylinder	No	90° - 10°
Power tilt	Option	
Connecting plate	Adaptator plate depending excavator model (on request)	
Quick coupler plate	Depending on required model (on request)	

Drifter

Drifter model	HD/RD1001-1002	
Rotative model	RH200	RH200 - RH220
Retraction force kN	15	
Max torque Nm	2 200	
Max speed rpm	364	

Radio remote control	Yes	
Radio remote with pressure indicators	Option	
Suggested excavator	Min 7T	Min 8T
Mounting type	Adaptator plate	

Clamping

Clamping type	Clamping	Clamping & Breaking (option)
Clamping range	30 - 76	25 - 135
Clamping force N	65 000	
Loosening torque Nm	18 500 Option	
Key of loosening	Option	

Hydraulic requirements

Oil requirements l/min	85 - 120	
Operating pressure bar	230	

Drilling operations

Case drilling mm	No	< 114
Rock drilling` diameter mm	38 - 51	
DTH drilling diameter mm	90	115
Self Anchor	R32-R38	R32-R38 / R51-R76
Drilling diameter mm	38 - 100	
Injection access	Yes	

Dimensions

Weight Kg (without safety cage)	1 100	1 160
Total Width mm	1 000	1 400
Total Length mm	5 300	5 550
Total Height mm	1 050	1 600