

## **TMF20**

## **Main Specifications**

Mast	
Mast type	CF200
Total length mm	5 700
Feed motion length mm	3 800
Feed shiffting length mm	1 500
Rollover	
Rollover type	360 °
Tip cylinder	No
Power tilt	Option

r cca similarig icriga	1 300	
Rollover		
Rollover type	360 °	
Tip cylinder	No	
Power tilt	Option	
Connecting plate	Adaptator plate depending excavator model (on request)	
Quick coopler plate	Depending on required model (on request)	
	-	

Drifter		
Drifter model	HD4010/RH800	
Rotative model	-	
Retraction force kN	50	
Max torque Nm	11 000	
Max speed rpm	248	

Radio remote control	Yes
Radio remote with pressure indicators	Option
Suggested excavator	Min 30T
Mounting type	Adaptator plate

Clamping		
Clamping type	Clamping & Breaking	
Clamping range	60 - 360	
Clamping force N	256 500	
Loosening torque Nm	92 800	
Key of loosening	Option	
Hydraulic requirements		
Oil requirements I/min	280 - 190	

230

Operating pressure bar

Drilling operations		
Case drilling mm	< 152	
Rock drilling` diameter mm	76 - 89	
DTH drilling diameter mm	> 150	
Self Anchor	R51-R76 - T114	
Drilling diameter mm	100 - 160	
Injection access	Yes	

Dimensions		
Weight Kg (without safety cage)	2 900	
Total Width mm	1 400	
Total Length mm	5 700	
Total Height mm	1 700	